



Specifications

DC Switch 600 A selector 4 pos

03-06-2022

ARTICLE NUMBER

50214711

DC Switch 600 A selector 4 pos

DIMENSIONS & WEIGHT

Weight (Kg)	0.59
Enclosure width	98 mm
Enclosure height	79 mm

GENERAL

Ambient operation temperature	-20 C ... +40C
Storage temperature	-25 C ... +85C
Operating humidity	95%, non condens

MECHANICAL

Connections terminal stud	M12 1/2")
Connections stud length	22mm
Maximum terminal Stud Torque	24.86 NM (220 in-lb)
Terminal material	tin-plated copper
Drilling mounting centers	76 mm
Rear panel mount diameter	92mm dia
Mounting screws	m6 screw
Ingress Protection Class	IP67
Enclosure Colour	RAL7024 Graphite Grey
Clearance	27.9 mm
Ignition Protection	UI 1500 SAE J1170
Markings	CE, Iso 8846

INPUT

Model type	Manual battery switch
Circuit type	selector 4 pos

Battery input	2
Switch Positions	4
Battery combine function	yes
I 10 Cranking rating 10 sec	2750A
I 60 Cranking rating 1 min	1150A
I 300 Cintermittent rating 5 min	700A
I C continue rating	500A
Vmno Voltage maxium Operation	32V DC