



# Specifications

## DC Switch 600 A on-off

03-06-2022

### ARTICLE NUMBER

50214711

DC Switch 600 A on-off

### DIMENSIONS & WEIGHT

Weight (Kg)	0.59
Enclosure width	98 mm
Enclosure height	79 mm

### GENERAL

Ambient operation temperature	-20 C ... +40C
Storage temperature	-25 C ... +85C
Operating humidity	95%, non condens

### MECHANICAL

Connections terminal stud	M12 1/2")
Connections stud length	22mm
Maximum terminal Stud Torque	24.86 NM (220 in-lb)
Terminal material	tin-plated copper
Drilling mounting centers	76 mm
Rear panel mount diameter	92mm dia
Mounting screws	m6 screw
Ingress Protection Class	IP66
Enclosure Colour	RAL7024 Graphite Grey
Clearance	27.9 mm
Ignition Protection	UI 1500 SAE J1170
Markings	CE, Iso 8845

### INPUT

Model type	Manual battery switch
Circuit type	on-off

Switch Positions	2
Battery combine function	-
I 10 Cranking rating 10 sec	2750A
I 60 Cranking rating 1 min	1325A
I 300 Cintermittent rating 5 min	900A
I C continue rating	600A
Vmno Voltage maxium Operation	32V DC