

KRAKEN BATTERY CHARGER PRODUCTS

AC-DC Chargers

Multi-Stage Charging

Product features:

- 3-Bank charging
- Selectable battery type
- Maximize battery life
- Microprocessor Controlled

Output Rating

Output Voltage
Output Current (Maximum)

12V
20A

12V
40A

DC Output

Selectable Battery Type
Charge
Float
Equalize (Flooded Battery Only)
Charging Control

Gel, AGM, Flooded, Lithium, Program

14.2 - 15.5V

14.2 - 15.5V

13.4 - 13.8V

14.2 - 15.5V

16.0V

16.0V

Three / Two Stages, Program

DC Output Bank
Parasitic Current

Three
<2mA

Three
<2mA

AC Input

Voltage (nominal)
Operation Range
Frequency Range
Power Consumption (full load)
Power Factor Correction

120, 230, 240VAC

120, 230, 240VAC

90 - 265VAC

90 - 265VAC

47 - 63Hz

47 - 63Hz

350W

700W

Yes

Yes

Protection

Reverse Battery
Cooling
Output Short Circuit
Ingress Protection

Yes

Yes

Forced Ventilation

Yes

Yes

IP 32

IP 32

Display Panel

Indicator
Digital Display (LED)

LCD with back lighting

Voltage, Current, Status and Error Code

Enclosure

AC Input Connection
DC Output Connection
Weight
Dimensions

Hardwire / AC Input Cord (Schuko, UK, Australia plug)

Heavy Duty Studs

5.3 lbs./2.4kg

5.7 lbs./2.6kg

11.6 x 8.1 x 3.4"
(295 x 206 x 86mm)

11.6 x 8.1 x 3.4"
(295 x 206 x 86mm)

Accessory (Optional)

Remote Panel
Battery Temp. Sensor

For viewing unit status, adjusting settings, and for connecting the chargers in parallel

For battery charging voltage adjustment

All specifications subject to change without notice.